

## Frame Technology

<b>Wheelsize</b>	29"
<b>Tire Clearance</b>	Clearance for 29 x 2.5" tires
<b>Fork</b>	Compatible with 120-140mm travel 29'er suspension forks
<b>Headset – Upper</b>	1-1/8" Zero Stack (ZS44/28.6)
<b>Headset – Lower</b>	For Tapered: 56mm zero stack (ZS56/40) For Straight: 56mm reducing zero stack (ZS56/30)
<b>Rear Shock Size</b>	190 x 50mm (7.5 x 2")
<b>Rear Shock Hardware</b>	8 x 22.2mm (both ends)
<b>Seatpost</b>	31.6mm
<b>Seat Collar</b>	35.0mm. Salsa Flip-Lock included, Black
<b>Front Derailleur</b>	High Direct Mount
<b>Bottom Bracket</b>	73mm English
<b>Crankset</b>	Any mountain crankset
<b>Rear Brake</b>	51mm I.S. Fits up to 185mm rotor
<b>Cable Routing</b>	Downtube cable routing uses full length housing. Dropper post housing guides for cleaner routing
<b>Rear Spacing</b>	142 x 12mm Maxle. Maxle included
<b>Derailleur Hanger</b>	FS2315
<b>Frame Weight</b>	6.5 to 7.0 lbs depending on frame size, including shock, seat collar, derailleur hanger, and Maxle
<b>Color</b>	Twister Grey